

RZ Codex 230 Natural Stone Sealer

Dirt and water-repellent protective coating for natural stone coatings

Range of application:

Sealing for the initial treatment of all surfaces of natural stone and cast concrete block, and quality stoneware. Cares for and protects against scratches, is dirt-repellent and slip-proof.

Suitable for:

- ▶ Natural stone
- ▶ Artificial stone
- ▶ Cast concrete block



Important reference:

Apply first-treatment products on the dry floor only after first cleaning and subsequent neutralization with clear water twice-undiluted has been implemented in the crossways process.

Product advantages/properties:

- ▶ Protects against severe stressing
- ▶ Does not form any dirt edges
- ▶ Dirt-repellent
- ▶ Slip-proof

Technical data :

Container type	Bottle (PE)
Delivery size	1000 ml
Shelf life	unlimited
Colour	transparent
Processing temp.	18 - 25 C°
Passable	After 12 - 16 hours
pH-value	9,1
Giscode	GE 20

Preparation:

Process floor covering with Codex RZ 110 Intensive Cleaner before the employment of Codex RZ 230 Natural Stone Seal. Application in accordance with usage description. Neutralize floor covering twice with clear water and allow floor covering to dry. Begin with the application following this.

Processing | First treatment:

1. Shake container before use for a short time and lightly
2. Place RZ 230 Natural Stone Seal into an oblong bucket, do not to pour directly onto the floor covering.
3. Immerse folding holders with fine-fiber mop in the bucket, scrape off at the edge and apply in straight strokes fully and undiluted
4. Do not wipe!
5. Allow surface to dry for 60 min., rinse mop.
6. Start second application at 90 degrees offset to the first.
7. Do not load floor for approx. 16 hours.
8. Floor can be used carefully after 5 hours
9. Clean working materials thoroughly.

Consumption: approx. 50ml / sqm
Range: approx. 20 sqm

Important references:

- ▶ Stable in original container with storage under uniform conditions for an unlimited period.
- ▶ It is important to protect against strongly fluctuating temperatures. Tightly close off containers already opened.
- ▶ Optimal processing at low to medium air humidity (approx. 65%) and normal room temperatures (18 - 30 degrees centigrade). High temperatures and low air humidity shorten the drying time
- ▶ It is absolutely necessary to subject surfaces cleaned with Codex RZ 230 Natural Stone Seal to a regular maintenance-cleaning with Codex RZ 310 Care Cleaner.
- ▶ Regular maintenance with RZ 310 Care Cleaner improves the optics and acts dirt-repellent.
- ▶ With the employment of Codex RZ 230 Natural Stone Seal, an expert consultation and/or implementation is advisable.

Work and environment protection:

Non-flammable, no irritant effects and not environmentally dangerous. It is possible that the contained and designated components of the perfumes, as well as the preservatives, can cause sensitizing or allergies with certain groups of persons. During processing, the utilization of skin protection cream, as well as the ventilation of the working areas, is basically recommended

Waste disposal:

Do not allow to enter undiluted into the sewage system, into water bodies or into the soil. Rinse out residue-emptied containers with a little water and dispose of as recycling-capable containers, in accordance with the local / official directives (DSD). The specifications are based on our experience and careful investigations. The quality of your work depends on professional construction site evaluation and product use by yourself. If in doubt, conduct a small sample test or obtain technical advice. The directions for use on the containers are to be strictly adhered to. With the issue of this product datasheet, all preceding product datasheets lose their validity.

09.02.2009 | FM