

Guarantee:

UZIN and DÖLLKEN provides a guarantee of 5 years on all the characteristics guaranteed in the fitting instructions.

- When laying the floor covering, take the generally accepted rules of the trade and technology and the applicable and valid national standard EN into account

Claims under the guarantee will be excluded if:

- Unusual influences affect the product, in particular of a chemical or mechanical nature.
- A utilisation or application has taken place that deviates from the installation instructions.
- If no steel pins/clamps have been used in the skirting ends in the cases of tension.

In all cases, some adhesion tests must be carried out on-site before carrying out the application.

PRODUCT DATA SHEET & APPLICATION INSTRUCTIONS

Special skirting tape for DÖLLKEN core skirting boards

Toptac 35

Secure gluing of DÖLLKEN core skirting boards

Product Properties / Benefits:

- ▶ DÖLLKEN – UZIN system guarantee
- ▶ Does not become brittle; permanent and reliable adhesion
- ▶ Clean indoor air
- ▶ Permanently flexible
- ▶ Quick installation even onto concrete and metal
- ▶ Easy to use with Toptac applicator



Applications:

▶ Suitable DÖLLKEN core skirting boards:

- DÖLLKEN core skirting board S 60
- DÖLLKEN core skirting board S 100
- DÖLLKEN core skirting board C 60
- DÖLLKEN core skirting board TS 60
- DÖLLKEN core skirting board TS 100

▶ Suitable walls:

- Breeze/plaster
- Brickwork
- Metal (untreated)
- Painted
- Synthetic material
- Wood
- Concrete
- Ceramics
- Plasterwork (primed)
- Wallpaper*
- Filled (primed)

▶ Not guaranteed:

- textile carpet skirting
- wooden baseboards
- aluminium skirting
- soft PVC skirting boards

* see „Preparation“

for < DÖLLKEN core skirting boards

ON > surfaces with up to 1 mm deep texture

Technical Data:

Special acrylic adhesive

Will not dry out or become brittle

Application temperature from + 15 °C

Temperature resistant from – 40 °C to + 140 °C (when installed)

Shelf-life min. 2 years in original packaging; store protected from direct sunlight

Do not place rolls on to the cut surfaces without adhesive-resistant paper washers inbetween


APPLICATION INSTRUCTIONS

Preparation:

- ▶ Preparation of the sub-surface: The sub-surface must be dry, hard, flat, able to be walked on and free of grease, dust and silicone, in accordance with the applicable, valid national standard EN.
- ▶ Wallpaper: must be firmly glued into place or be cut back to the height that will be covered by the skirting.
- ▶ Storage/Transport: Do not roll the core skirting boards (builds-up tension).
- ▶ Binding the dust: any dust must be consolidated with a solvent-free primer.

What you need:

- ▶ Toptac 35, Toptac applicator, rubber hammer, carpet knife



1

- ▶ Pull up and lock the roll holder
- ▶ Fit the adhesive-repellent paper washer



2

- ▶ Depending on the direction of work, place the Toptac 35 in the applicator running to the left or the right
- ▶ Lower the roll holder



3

- ▶ Apply the Toptac 35 to the wall using the applicator
- ▶ For TS 100 and S 100, apply a second strip of Toptac 35 by hand, directly above the first strip



4

- ▶ Remove the Toptac protective paper
- ▶ Fit the core skirting board to the Toptac 35
- ▶ Tap in all over using the rubber hammer



Toptac applicator:

- ▶ Handling: This is a precision device, and must be protected from pressure, impacts and falls.
- ▶ Cleaning: Dab off adhesive remnants with SUPERTape 7900 or remove using sewing machine oil. Do not use any solvents, as the adhesive could smear.
- ▶ Tip: If tensions appear in the core skirting board (for example, as a result of uneven walls), fit a steel pin at the ends of the skirting.

Fitting of outer (1-2) and inner (3-4) corners

1

- ▶ Run beyond the corner up to the centre of the applicator head



2

- ▶ Swivel the rear pressure roller away from the wall
- ▶ Turn the device around the corner in such a way that the applicator head remains in contact with the wall



3

- ▶ Run the applicator into the corner
- ▶ Turn the applicator head over



4

- ▶ Run into the corner with the pressure roller and continue running with the Toptac applicator
- ▶ Cut through the Toptac 35 in the corner



Punching:

After fitting the Toptac 35, adapt the DÖLLKEN core skirting board free of tension according to the manufacturer's instructions

